

underside of a vehicle to prevent the inadvertent transfer of lead contaminated material to another area of a secondary lead smelter or to public roadways.

Wet suppression means the use of water, water combined with a chemical surfactant, or a chemical binding agent to prevent the entrainment of dust into the air from fugitive dust sources.

§ 63.543 Standards for process sources.

(a) No owner or operator of a secondary lead smelter shall discharge or cause to be discharged into the atmosphere from any existing, new, or reconstructed blast, reverberatory, rotary, or electric smelting furnace any gases that contain lead compounds in excess of 2.0 milligrams of lead per dry standard cubic meter (0.00087 grains of lead per dry standard cubic foot).

(b) [Reserved]

(c) No owner or operator of a secondary lead smelter with a collocated blast furnace and reverberatory furnace shall discharge or cause to be discharged into the atmosphere from any existing, new, or reconstructed blast furnace or reverberatory furnace any gases that contain total hydrocarbons in excess of 20 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide, except as allowed under Paragraphs (c)(1) and (c)(2) of this section.

(1) No owner or operator of a secondary lead smelter with a collocated blast furnace and reverberatory furnace shall discharge or cause to be discharged into the atmosphere from any existing blast furnace any gases that contain total hydrocarbons in excess of 360 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide, during periods when the reverberatory furnace is not operating.

(2) No owner or operator of a secondary lead smelter with a collocated blast furnace and reverberatory furnace shall discharge or cause to be discharged into the atmosphere from any blast furnace that commences construction or reconstruction after June 9, 1994, any gases that contain total hydrocarbons in excess of 70 parts per million by volume, expressed as propane corrected to 4 percent carbon di-

oxide, during periods when the reverberatory furnace is not operating.

(d) No owner or operator of a secondary lead smelter with only blast furnaces shall discharge or cause to be discharged into the atmosphere from any existing blast furnace any gases that contain total hydrocarbons in excess of 360 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide.

(e) No owner or operator of a secondary lead smelter with only blast furnaces shall discharge or cause to be discharged into the atmosphere from any blast furnace that commences construction or reconstruction after June 9, 1994, any gases that contain total hydrocarbons in excess of 70 parts per million by volume, expressed as propane corrected to 4 percent carbon dioxide.

(f) If the owner or operator of a blast furnace or collocated blast furnace and reverberatory furnace combines the blast furnace charging process fugitive emissions with the blast furnace process emissions and discharges them to the atmosphere through a common emission point, then compliance with the applicable total hydrocarbon concentration limit under paragraph (c) of this section shall be determined downstream from the point at which the two emission streams are combined.

(g) If the owner or operator of a blast furnace or a collocated blast furnace and reverberatory furnace does not combine the blast furnace charging process fugitive emissions with the blast furnace process emissions and discharges such emissions to the atmosphere through separate emission points, then the total hydrocarbon emission rate for the blast furnace process fugitive emissions shall not be greater than 0.20 kilograms per hour (0.44 pounds per hour).

(h) Except as provided in paragraph (i) of this section, following the initial test to demonstrate compliance with paragraph (a) of this section, the owner or operator of a secondary lead smelter shall conduct a compliance test for lead compounds on an annual basis (no later than 12 calendar months following the previous compliance test).

(i) If a compliance test demonstrates a source emitted lead compounds at 1.0

Environmental Protection Agency

§ 63.544

milligram of lead per dry standard cubic meter (0.00044 grains of lead per dry standard cubic foot) or less during the time of the compliance test, the owner or operator of a secondary lead smelter shall be allowed up to 24 cal-

endar months from the previous compliance test to conduct the next annual compliance test for lead compounds.

(j) The standards for process sources are summarized in table 2.

TABLE 2.—SUMMARY OF STANDARDS FOR PROCESS SOURCES

Furnace configuration	Lead compounds (milligrams per dry standard cubic meter)	Total hydrocarbons	Citation
Collocated blast furnace and reverberatory furnace:			
When both furnaces operating ..	2.0	20 parts per million by volume ¹	§ 63.543(a),(c).
When reverberatory furnace not operating.	2.0	360 parts per million by volume ¹ (existing).	§ 63.543(a),(c)(1).
.....	70 parts per million by volume ¹ (new) ² .	§ 63.543(a),(c)(2).
Blast	2.0	360 parts per million by volume ¹ (existing).	§ 63.543(a),(d).
.....	70 parts per million by volume ¹ (new) ² .	§ 63.543(e).
.....	0.20 kilograms per hour ³	§ 63.543(g).
Reverberatory, rotary, and electric ...	2.0	Not applicable	§ 63.543(a).

¹ Total hydrocarbons emission limits are as propane at 4 percent carbon dioxide to correct for dilution, based on a 3-hour average.

² New sources include those furnaces that commence construction or reconstruction after June 9, 1994.

³ Applicable to blast furnace charging process fugitive emissions that are not combined with the blast furnace process emissions prior to the point at which compliance with the total hydrocarbons concentration standard is determined.

§ 63.544 Standards for process fugitive sources.

(a) Each owner or operator of a secondary lead smelter shall control the process fugitive emission sources listed in paragraphs (a)(1) through (a)(6) of this section in accordance with the equipment and operational standards presented in paragraphs (b) and (c) of this section.

(1) Smelting furnace and dryer charging hoppers, chutes, and skip hoists;

(2) Smelting furnace lead taps, and molds during tapping;

(3) Smelting furnace slag taps, and molds during tapping;

(4) Refining kettles;

(5) Dryer transition pieces; and

(6) Agglomerating furnace product taps.

(b) Process fugitive emission sources shall be equipped with an enclosure hood meeting the requirements of paragraphs (b)(1), (b)(2), or (b)(3) of this section, or be located in a total enclosure subject to general ventilation that maintains the building at a lower than ambient pressure to ensure in-draft through any doorway opening.

(1) All process fugitive enclosure hoods except those specified for refining kettles and dryer transition pieces shall be ventilated to maintain a face velocity of at least 90 meters per minute (300 feet per minute) at all hood openings.

(2) Process fugitive enclosure hoods required for refining kettles in paragraph (a) of this section shall be ventilated to maintain a face velocity of at least 75 meters per minute (250 feet per minute).

(3) Process fugitive enclosure hoods required over dryer transition pieces in paragraph (a) of this section shall be ventilated to maintain a face velocity of at least 110 meters per minute (350 feet per minute).

(c) Ventilation air from all enclosures hoods and total enclosures shall be conveyed to a control device. Gases discharged to the atmosphere from these control devices shall not contain lead compounds in excess of 2.0 milligrams of lead per dry standard cubic meter (0.00087 grains per dry standard cubic foot).

(d) All dryer emission vents and agglomerating furnace emission vents